


AC AXIAL FANS

Model No.	Bearing ● Sleeve ● Ball	Voltage V	Frequency Hz	Current A	Input Power W	Speed RPM	Airflow CFM	Static Pressure mm H ₂ O	Noise dB(A)	Box Pkg. Pcs.

80 x 80 x 25 mm

28025 A1 M W	○	115	50/60	0.12/0.10	12/11	2400/3000	18/22	3.0/3.7	29/30	40
28025 A2 M W	○	230	50/60	0.07/0.05	13/11	2400/3000	22/25	3.2/4.5	29/30	40



120 x 120 x 38 mm

22038 A1 M T/W	○	115	50/60	0.21/0.18	18/17	2550/2850	80/105	6.4/7.6	43/48	40
22038 B1 M T/W	●	115	50/60	0.21/0.18	18/17	2600/2900	85/110	6.4/7.6	43/48	40
22038 A2 M T/W	○	230	50/60	0.12/0.11	22/20	2550/2850	80/105	6.4/7.6	43/48	40
22038 B2 M T/W	●	230	50/60	0.12/0.11	22/20	2600/2900	85/110	6.4/7.6	43/48	40
22038 A24 M T	○	24	50/60	0.88/0.80	18/17	2550/2850	80/105	6.4/7.6	43/48	40
22038 B24 M T	●	24	50/60	0.88/0.80	18/17	2600/2900	85/110	6.4/7.6	43/48	40



Ø 172 x 150 x 51 mm

21725 A1 M W	○	115	50/60	0.38/0.37	30/29	2500/2800	175/180	12.2/9.7	52/55	20
21725 B1 M W	●	115	50/60	0.38/0.37	30/29	2600/2900	180/200	12.2/9.7	52/55	20
21725 A2 M W	○	230	50/60	0.23/0.20	37/35	2500/2800	175/180	12.2/9.7	52/55	20
21725 B2 M W	●	230	50/60	0.23/0.20	37/35	2600/2900	180/200	12.2/9.7	52/55	20



★ Fan with AC to DC Converter

21725 B2 M W X	●	230	50/60	0.147	20	3300	280	12	52	20
----------------	---	-----	-------	-------	----	------	-----	----	----	----

Ø 220 x 60 mm

22060 R B1 M W	●	115	50	0.77	62	2300	360	22	56	10
22060 R B2 M W	●	230	50	0.42	65	2300	360	22	56	10



★ Fan with AC to DC Converter

22060 R B2 W X	●	230	50/60	0.22	30	3000	450	28	60	10
----------------	---	-----	-------	------	----	------	-----	----	----	----

EXHAUST FANS

125 x 125 x 38 mm

22538 A2 M W	○	230	50/60	0.12/0.11	22/20	2550/2850	80/105	6.4/7.6	43/48	40
--------------	---	-----	-------	-----------	-------	-----------	--------	---------	-------	----



172 x 172 x 55 mm

27255 A1 M W	○	115	50/60	0.38/0.37	30/29	2500/2800	175/180	12.2/9.7	52/55	20
27255 B1 M W	●	115	50/60	0.38/0.37	30/29	2600/2900	180/200	12.2/9.7	52/55	20
27255 A2 M W	○	230	50/60	0.23/0.20	37/35	2500/2800	175/180	12.2/9.7	52/55	20
172-55T B2 M W	●	230	50/60	0.23/0.20	37/35	2600/2900	180/200	12.2/9.7	52/55	20



220 x 220 x 60 mm

22060 S A2 M W	○	230	50	0.42	65	2300	360	22	56	10
220-60 T B2 M W	●	230	50	0.42	65	2300	360	22	56	10

